



CHARACTERISTICS	
LOAD:	1000 Kg
PERSONS:	13
RATED SPEED	1 m/s VF
TRAVEL:	- mm
FLOORS:	-
SEQUENCE:	-
MACHINE DENOMINATION:	DMM-10-1000-2S
TRACTION PULLEY:	ø330
DEFLECTION PULLEY:	ø400
SUSPENSION:	2-1
TRACTION ROPES:	6x8ø
OVERSPEED GOV. ROPE:	ø6
CWT GUIDE RAIL:	65/54/8
CAR GUIDE RAIL:	90/75/16
CWT SAFETY GEAR: (if required)	-
CAR SAFETY GEAR	F2S
CAR BUFFER(2):	ø100/80
CWT BUFFER(2):	ø100/80
MACHINE POWER:	9,6 CV
POWER VOLTAGE:	380 V
LIGHTING VOLTAGE:	220 V
PHASES:	3
NOMINAL CURRENT:	14,2 A
START CURRENT	14,2 A
R1:	28,042 N
R2:	41,202 N
R3:	31,392 N
R4:	19,208 N

DENOMINATION		POS MATERIAL WEIGHT		DRAWING	
Nº OF PIECES	2008	Date:	20-10	Nome:	VGM
GROUP	4 3 2 1	Drawn:	20-10	Checked:	20-10
CUSTOMER		Scale:		GRL 1000	
S-E		Subs. Draw N.º:		I-2/-	
Replaced by:		Ed.0		Falesa	
				FABRICACION DE ELEVADORES S.L.	